```
L17 ANSWER 1 OF 1 CAPLUS COPYRIGHT 2006 ACS on STN
     1979:73465 CAPLUS
AN
DN
     90:73465
ED
    Entered STN: 12 May 1984
    Dry decalcomania
ΤI
     Bartz, Jan; Tanasiewicz, Stanislaw
IN
     Zjednoczone Zaklady Ceramiki Stolowej "Cerpol", Pol.; Walbrzyskie Zaklady
PA
     Graficzne "Kalkomania"
so
     Pol., 3 pp.
     CODEN: POXXA7
DТ
    Patent
LA
    Polish
IC
    B41M003-12
    42-13 (Coatings, Inks, and Related Products)
CC
FAN CNT 1
    PATENT NO.
                        KIND
                              DATE
                                         APPLICATION NO.
                                                               DATE
     _____
                       ----
                              _____
                                          -----
                                                                -----
    PL 87649
                        P
                              19760731
                                        PL 1973-167862 19731231 <--
PRAI PL 1973-167862
                       Α
                              19731231
CLASS '
              CLASS PATENT FAMILY CLASSIFICATION CODES
 PATENT NO.
 _____
 PL 87649
               IC B41M003-12
               IPCI
                      B41M0003-12
    Decals were obtained on polyethylene (I) [9002-88-4] film supports for
AB
    transfer to wood, paper, ceramics, or glass. Thus, an ink paste was
    obtained by dispersing carbon black in Bu methacrylate-ethylene
     acrylate-ethylene methacrylate-Me methacrylate copolymer [31942-54-8] and
     4:1 Tetralin-methoxybutyl acetate mixture The paste (100 parts) was
     combined with 45 parts Izocyn PT [39301-06-9] and used for the
     screen-printing of I film. After drying the printed side was coated with
     an adhesive containing polyisobutylene (II) [9003-27-4] (mol. weight 15,000)
12.
    II (mol. weight 50,000) 5, II (mol. weight 100,000) 3, solvent naphtha 70,
    pyrolytic silica 6, bentonite 2, tetraallylammonium chloride 1, and rice
     starch 1 part. The printed design could be transferred to any smooth
     surface by applying slight pressure to the I side.
ST
    decal polyethylene film backing; methacrylate copolymer decal ink
IT
    Urethane polymers, uses and miscellaneous
    RL: USES (Uses)
        (binders, for inks, for decals)
    Decalcomanias
IΤ
       (polyethylene backings for)
IT
    9003-27-4
    RL: USES (Uses)
       (adhesives, for decals)
ΙT
    39301-06-9
    RL: USES (Uses)
       (binders, for inks, for decalcomania)
ΙT
    31942-54-8
    RL: USES (Uses)
       (binders, for inks, for decals)
IT
    9002-88-4
    RL: USES (Uses)
       (decalcomania backings)
RN
    9003-27-4
RN
    39301-06-9
RN
    31942-54-8
RN
    9002-88-4
```